

IN THE CLAIMS

1. (currently amended) A golf cart comprising:

at least one external surface; and

an apparatus for coupling a glove to said at least one external surface, said apparatus comprising a body comprising an inner surface and an ~~opposite~~ outer surface ~~that extends between a first end and an opposite second end~~, said body ~~being a flexible sheet material coupled to said golf cart such that said body conforms to a shape of said at least one external surface~~, said inner surface remains in substantial contact against said at least one external surface during operation of said golf cart, ~~and said inner surface is substantially concentrically aligned with said at least one external surface~~, said body comprising at least one first fastening mechanism coupled to said body inner surface, said at least one first fastening mechanism coupling said body to said at least one external surface of said gold cart, said body outer surface comprising at least one second fastening mechanism for removably coupling a glove to said body such that the glove remains coupled to said apparatus during operation of said golf cart.

2. (currently amended) A golf cart in accordance with Claim 1 wherein said ~~body inner surface comprises at least one fastening mechanism for securing said body against said at least one external surface~~, said inner surface first fastening mechanism comprising comprises at least one of an adhesive, a mechanical fastening device, an interlocking device, a hook and loop fastener, a hook and pile fastener, a tab and slot device, a locking mechanism, a magnet, and a tying system.

3. (currently amended) A golf cart in accordance with Claim 1 wherein said body further comprises at least one third fastening mechanism configured to secure said body inner surface against said at least one external surface.

4. (currently amended) A golf cart in accordance with Claim 1 wherein said ~~body~~  
~~outer surface comprises at least one~~ second fastening mechanism removably couples the  
glove to said apparatus such that the glove is suspended from said body.

5. (currently amended) A golf cart in accordance with Claim 1 wherein ~~said body~~  
~~outer surface comprises at least one fastening mechanism for removably coupling a glove to~~  
~~said body, said outer surface~~ second fastening mechanism comprises at least one of a  
mechanical fastening device, an interlocking device, a hook and loop fastener, a hook and  
pile fastener, a tab and slot device, a locking mechanism, a magnet, and a tying system.

6. (original) A golf cart in accordance with Claim 1 wherein said apparatus  
facilitates drying a damp golf glove.

7. (currently amended) A golf cart comprising:

a passenger compartment;

~~at least one frame support adjacent to said passenger compartment;~~

a dashboard adjacent to said passenger compartment;

a roof extending over at least a portion of said passenger compartment; and

a glove drying system coupled to an external surface of at least one of said passenger  
compartment, ~~said at least one frame support, said dashboard, and said roof, said golf drying~~  
~~system comprising a first end, a second end, and a body extending therebetween, said body~~  
~~being a flexible sheet material comprising an inner surface and an opposite outer surface, said~~  
~~body coupled to said golf cart such that said body conforms to a shape of said golf cart~~  
~~external surface, substantially all of said inner surface remains against said golf cart external~~  
~~surface during operation of said golf cart, and said inner surface is substantially~~  
~~concentrically aligned with the external surface, said body outer surface comprises at least~~  
one fastening mechanism for removably coupling a glove to said system such that the glove

remains coupled to said fastening mechanism between said first end and said second end during operation of said golf cart.

8. (currently amended) A golf cart in accordance with Claim 7 wherein said ~~outer surface comprises~~ at least one fastening mechanism removably couples the glove to said system such that the glove is suspended from said system.

9. (currently amended) A golf cart in accordance with Claim ~~87~~ wherein said ~~outer surface~~ at least one fastening mechanism comprises at least one of a mechanical fastening device, an interlocking device, a hook and loop fastener, a hook and pile fastener, a tab and slot device, a locking mechanism, a magnet, and a tying system.

10. (currently amended) A golf cart in accordance with Claim ~~87~~ wherein said at least one fastening mechanism is an at least one first fastening mechanism, and said inner surface comprises a at least one second fastening mechanism for securing said body against said golf cart external surface, said ~~inner surface~~ at least one second fastening mechanism comprising at least one of an adhesive, a mechanical fastening device, an interlocking device, a hook and loop fastener, a hook and pile fastener, a tab and slot device, a locking mechanism, a magnet, and a tying system.

11. (currently amended) A golf cart in accordance with Claim ~~87~~ wherein said at least one fastening mechanism is an at least one first fastening mechanism, and said body further comprises at least one second fastening mechanism configured to secure said body inner surface against said golf cart external surface.

12. (currently amended) A golf cart in accordance with Claim ~~87~~ wherein said glove drying system facilitates drying a damp golf glove.

13. (currently amended) A method of drying a damp golf glove, said method comprising:

providing a golf glove drying system that includes a body having an inner surface and an ~~opposite~~ outer surface ~~and being a flexible sheet material such that each surface extends~~ extend between a first end and an opposite second end;

coupling the golf glove drying system to the golf cart such that ~~the body conforms to a shape of at least one external surface of the golf cart,~~ substantially all of the body inner surface between the first end and the second end remains in contact with ~~an~~ the external surface of the golf cart during operation of the golf cart, ~~and the inner surface is substantially concentrically aligned with the external surface of the golf cart;~~

securing the golf glove drying system to the external surface of the golf cart using at least one first fastening mechanism adjacent the body first end and at least one second fastening mechanism adjacent the body second end; and

removably coupling a golf glove to the golf cart using at least one third fastening mechanism extending from the body outer surface, such that the golf glove remains suspended from the golf glove drying system between the first end and the second end during operation of the golf cart.

14. (original) A method in accordance with Claim 13 wherein coupling the golf glove to the golf cart further comprises coupling the golf glove to the body outer surface using at least one of a mechanical fastening device, an interlocking device, a hook and loop fastener, a hook and pile fastener, a tab and slot device, a locking mechanism, a magnet, and a tying system.

15. (original) A method in accordance with Claim 13 wherein coupling the golf glove drying system to the golf cart further comprises coupling the body against the golf cart external surface using at least one of an adhesive, a mechanical fastening device, an interlocking device, a hook and loop fastener, a hook and pile fastener, a tab and slot device, a locking mechanism, a magnet, and a tying system.